



Technical information

ESD UniClean

All purpose cleaner



Technical Data

Density at 25°C	0,9860g/cm³
Viscosity at 20°C	9,0 mPas
pH-value at 20°C	7,0 at 30g/l
Explosion risk	none
Solubility in water	unlimited
Application temperature	20°C
Application	ready-to-use/1:10
Storing frost-free	in original container
Waste key	07 06 99
WPC	2
Hazards classification	no marking required

All purpose cleaner especially for ESD equipment, stripe free and antistatic.

ESD UniClean is a neutral cleaner for all kinds of working tables, shelves and equipment.

It has antistatic properties and is dust repellent. The electrostatic charge will be suppressed on screens. Not suitable for plexiglass.

The cleaner can be used as ready-to-use liquid or diluted with water in a 1:10 ratio. Simply spray onto the surface or apply with a rag and wipe clean while still wet. Do not let liquid penetrate into the equipment.

Applications

Cleans:	
working tables	++*
shelves	++*
equipment	++*
screens	++*

For commercial use only!

Your ESD UniClean supplier:

Process

	Manual cleaning

Part No. 090606-10 // Contents 10l

Part No. 090606-5 // Contents 2 x 5l

Made in Germany

Part No.

***++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended**

Note: The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime concentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner configuration. Such tests may be carried out directly at the **kolb** Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

Kolb Cleaning Technology GmbH
 Karl-Arnold-Str. 12 · D - 47877 Willich
 Further information: www.kolb-ct.com

Phone +49 (0) 2154 9479 - 38
 Fax +49 (0) 2154 9479 - 47
 e-mail info@kolb-ct.com

All modifications due to technical improvements are subject to change without notice.